# RDA Port-A-Weld System (PWS)

PWS6x6

#### Self-Contained System

facilitates power source, column and boom on a mobile platform, providing a compact, turnkey welding solution with multiple welding processes including SAW, GMAW and GTAW

#### **Built-In Fork Pockets and Caster Wheels**

provide mobility options to move the welding system to your workpiece

#### Easy Positioning of the Weld Head

through use of integrated motorized column, manual telescoping boom, cross slides and 360-degree column rotation

#### **Manual Cross Slides**

provide 7.87" (200 mm) of fine vertical and horizontal welding head adjustment

#### Motorized Column with Pendant Control

provides 29.5" (750 mm) minimum to 78.7" (2000 mm) maximum under-boom vertical travel to accommodate weldments of various heights

#### Specifications

Max Height Under Boom	Min Height Under Boom	Lift Motor	Vertical Boom Travel	Column Rotation	Control Box Functions	Remote Pendant Control Functions
78.7" (2000 mm)	29.5" (750 mm)	0.37 kW	57:1" (1450 mm)	Manual 360°, lockable	Up/down/stop/speed control	Up/down/stop/speed control

Primary Input Power	Input Current at Rated Load	Overall Height	Weight	Control Box Ingress Protection Rating	Optional
115 VAC	16 A	100" (2540 mm)	1,235 lb (560 kg)	IP65	Motorized in/out boom travel

# Rental | Lease | Purchase





### RDA Port-A-Weld System (PWS)



## For more information 1-866-733-3272 | reddarc.com | Automation-sales@airgas.com

Specifications are subject to change without notice