
Studhorse 1000DM

1000 AMP Inverter Power Source



•5-YR GUARANTEE AGAINST CORROSION-RELATED FAILURES IN NATURAL ENVIRONMENTS•



The only
SCR-type
inverter welder
made in
the U.S.A.

MANUFACTURED BY



...probably the toughest welders on the planet

ARCON WELDING EQUIPMENT (LLC)

2203 Northwood Drive, Bldg.10, Salisbury, MD 21801
Phone: 410.572.6000 • Fax: 410.572.6027
Toll Free: 888.512.7266

sales@arconweld.com • www.arconweld.com

• Portable and Lightweight for Industrial Stud Welding

• 4 per Minute Duty Cycle @ 1000 Amps for 5/8" Studs

Stepless Weld Power and Time Adjustment

• 5-year Corrosion Protection Guarantee in Natural Environments

BENEFITS

- Lightweight, Portable
- Regulated Output
- Welds Wide Range of Sizes
- Reliable SCR Inverter
- Rugged Fiberglass Case
- 100% Corrosion Protected
- Pilot Current
- Kick Start
- After Burn
- Short-Circuit Protection
- High Power Efficiency
- 5-Zones of Thermal Protection



FEATURES

- Drawn Arc Stud Welding up to 1000 Amps
- Welds full-base Studs from 1/4" (6mm) to 5/8" (16mm)
- Complete systems available with gun and cables
- Digital Start/Stop replaces mechanical Contactor
- Bright, easy to read digital display
- Extra-thick skids on the bottom of the case for protection
- Stepless 0.05 to 1.00-second Time Control
- 400V or 480V three-phase input voltage; 35/30A time-delay fusing


PROVEN RELIABILITY
RUGGED CONSTRUCTION
GREAT WELDING CHARACTERISTICS

Studhorse 1000DM Specifications

Primary Input	Duty Cycle For Continuous Operation	Open Circuit Voltage	Recommended Fusing		кw	Efficiency	Physical Dimensions	Weight	
			400V	480V				Net	Ship
400V or 480V Three Phase	5/8" 4/min 1/2" 6/min 5/16" & 3/8" 8/min 1/4" unlimited	8V	35A "slow blow"	30A "slow blow"	23.8	79%	Height: 17.9" 45.5cm Width: 10.5" 26.7cm Depth: 19.5" 49.5cm	Approx. 80lbs. 36.3kg.	Approx. 90lbs. 41.0kg.

400V or 480V SINGLE VOLTAGE "Slow Blow Fuse"

The Workhorse product line is designed for use in harsh environments including construction, shipbuilding, boiler manufacturing and equipment fabrication. **Studhorse power** sources weigh 80 pounds, feature a built-in circuit breaker. and provide 5-zones of thermal protection to make this machine ideal for companies and contractors using 400 or 480 Volts AC for primary power. **Designed for 1200A** using 50 ft. 2/0 cable or 75 ft. of 4/0 cable.



Product Specifications are subject to change without notice. Visit the website for information on updates and changes.

Additional information is available at www.arconweld.com or from the Distributor listed below.

Manufactured by



www.arconweld.com

Products from ARCON

Welding Equipment



Workhorse 300S Stick/Lift Start TIG



Workhorse 300MS MIGweld



Wire Feeders WF200R and WF400R



Workhorse 300ST **ArcStarter TIG**



Studhorse 1000DM &1200DM Stud Welders



Ironhorse 300S 700V DC Input