

Red-D-Arc Welderrentals

When you're ready to weld.

Red-D-Arc Welderrentals is North America's leading provider of rental welding products and services, with over 50,000 units in a fleet that includes welders, welding positioners and other welding-related equipment, for almost any type of welding process and application.

D550K HO Diesel Welder




PORTABLE DC CC CV WELDING

EXTREME-DUTY SPECIFICATIONS

KUBOTA V3300-B DIESEL ENGINE POWER

20 kW 240 VAC AUXILIARY POWER



1-866-733-3272

Rental Centers Across North America

D550K HO Diesel Welder

Processes

Stick, MIG, DC TIG, Flux-Cored Welding and Air Carbon Arc Gouging

Description

The D550K HO is a 500 amp @ 100% duty cycle, constant current, constant voltage, DC, diesel engine-driven welder with an available 20,000 watts 240 VAC auxiliary power. Its three-phase rotating field generator produces a smooth DC weld output and has enough power for gouging with up to 3/8" carbons. A simplified control panel provides easy process set-up and includes a five-position Amperage Control switch, a potentiometer-type Voltage/Amperage Adjust Control for fine-control, and a six-position Process/Contactor Control switch. Remote contactor control, as well as remote amperage and voltage control, are via a 14-pin receptacle mounted on the front control panel.

Engine

Kubota V3300-B liquid-cooled, four cylinder, 49.5 HP diesel engine

Features

25 gallon (95 litre) fuel tank
 Body constructed of 304 brushed stainless steel sheet metal for enhanced durability
 15-stage process epoxy-electrocoated fully-enclosed base (e-coat)
 Rugged, simple control panel
 Remote oil drain and easy-access fuel drain
 Low oil pressure and temperature safety shutdown
 Standard front-panel mounted Engine hour meter, Fuel gauge, Battery ammeter and Engine temperature gauge
 120 V 20 A GFCI receptacle, 240 V 20 A twistlock receptacle, 120/240 V 50 A receptacle, 240 V 48 A 3-phase connection

Options

195 511 PRHC-14 Remote hand current and contactor control with 120 VAC GFCI power to the operator
 195 095 Polarity reversing/AC switch for AC-TIG welding (optional high-frequency unit also available)
 Extreme-Duty protective frame
 5+20/HO Construction Trailer

Specifications

DC AMPERAGE RANGE	20 - 600 A		
MAXIMUM OCV	95 in CC/DC welding mode		
	56 in CV/DC welding mode		
RATED CC OUTPUT	500 A at 40 VDC, 100% duty cycle		
	600 A at 44 VDC, 40% duty cycle		
DC VOLTAGE RANGE	14 - 40 V		
	MAXIMUM AC OUTPUT	Welding	Not-Welding
		Single-Phase	4,000 watts
or Single-Phase	4,000 watts		
Three-Phase	20,000 watts		
WEIGHT	No fuel: 1808 lb (820 kg)		
FUEL CAPACITY	25 gallons (95 L)		
DIMENSIONS	H: 50" (1270 mm)		
	W: 30.75" (781 mm)		
	L: 69.5" (1765 mm)		
OPERATOR MANUAL	OM-243 907G		
TECHNICAL MANUAL	N/A		

Control Panel

