## **Red-D-Arc Welderentals**

## **Calibration** Certificate

Unit Serial Number:LH320166GInstrument Number:8470842IP Address:192.168.111.222

Date Tested:20-Jun-17Mac Address:00:0A:8D:81:41:3A

Primary Standard							
	382 (F)		882 (F)		1382 (F)		
	Signal Voltage	Recorder display	Signal Voltage	Recorder display	Signal Voltage	Recorder display	
Channel 1	2.789	382	6.018	882	9.240	1382	
Channel 2	2.796	383	6.024	884	9.248	1384	
Channel 3	2.792	382	6.025	883	9.248	1383	
Channel 4	2.802	384	6.030	885	9.255	1384	
Channel 5	2.798	383	6.020	883	9.256	1385	
Channel 6	2.797	383	6.027	884	9.258	1385	

## Allowable difference in temp reading is +or- 5 Deg. F.

## **Instruments Used:**

Fluke 714 Thermocouple Cali	brator SN: 2097001	Calibration Date: 13-Mar-17
Precision digital multimeter	SN: 2142012	Calibration Date: 13-Mar-17

ProHeat 35 power supply used for signal output SN: ME040114G Calibration date: 20-Jun-17

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.

Technician:

Calibration due date: 20-Jun-18

Signature