

CALGARY 2022-2024 LIDAR DIGITAL ELEVATION MODEL

Data Steward Contact: Geospatial Business Solutions, GBS@Calgary.ca

Updated: 2025/03/25

Metadata for DEM LIDAR 2022-2024

The DEM is a raster elevation dataset of ground surface topography, generated from aerial lidar measurements. The bare-earth surface is classified by algorithms, which keeps ground, road and water surfaces but excludes other captured above ground features such as buildings, trees and power lines. Lidar has the capability to capture ground information underneath trees and other vegetation as long as the emitted light beams are able to penetrate between the foliage.

The lidar data was captured using a fixed wing aircraft equipped with special aerial lidar sensors and high accuracy GNSS/INS positioning systems to gather direct range measurements of ground surface features at approximately 25 points per square meter (that's over 30 billion points across the entire city).

This data is commonly used for many applications such as 3D spatial analysis (slope calculation, cross section creation, volumetric computations), for engineering applications (road design, land development, flood modelling) and 3D terrain visualization.

Within Calgary, this DEM contains lidar bare earth data from aerial lidar surveys done in 2022 and 2024. 2024 lidar data was incorporated in areas of larger known terrain change, such as at new neighbourhoods, new roadways and new buildings. (~20% of the city)

- LIDAR Survey Date: Calgary citywide coverage - May 26-30, 2022
2024 updated areas flown - June 12-14, 2024
City landfill areas flown - October 19 & 24, 2024
Areas beyond the city limits were captured from 2012 to 2024.
See the [Lidar Coverage Web App](#) or `calgis.lidar_coverage` for details.
- DEM File format: ArcGrid .ASC or GeoTiff .TIF
- DEM grid spacing: 20 cm (1 m and 2 m also available)
- Point Density: 25 points per square meter (average)
- Airborne Sensor: Teledyne Optech Galaxy T2000 & Riegl LMS-Q560
- Vertical Accuracy: +/- 5 cm at 95% confidence level on flat, hard surfaces
(confirmed with 200+ surveyed ground control points)

Note that for areas with no bare-Earth LIDAR returns, the elevations are interpolated from the nearest available bare-Earth LIDAR points. For example, within building footprints, underneath dense vegetation or underneath bridges and overpasses.

The DEM is tiled by Alberta Township System (ATS) Sections. File naming is Section-Township-Range-Meridian. (i.e. SSTTRRM.asc)

Internal Webpage: [DEM from Lidar Product Page](#)

The City of Calgary Geospatial Coordinate System

- Name: 3TM NAD83 Alberta 114W
- EPSG Code: 3776
- Projection: Transverse Mercator – 3TM (3 degree zone width)
- Horizontal Datum: NAD83 (Adopted/Original)
- Ellipsoid: GRS80
- Central Meridian: 114°00'00.0" W
- Scale Factor: 0.9999
- Origin Latitude: 0°00'00.0" N
- False Easting: 0 m
- False Northing: 0 m
- Positive Axes: North and East
- Planar Units: Meters
- Vertical Datum: CGVD28
- Geoid Model: GSD95 (ITRF version)
- Elevations: Orthometric (above mean sea level)
- Vertical Units: Meters

COPYRIGHT © 2024 The City of Calgary

All rights reserved. No part of this propriety product may be reproduced in any form or by any means without the written consent of The City of Calgary and a license agreement. The City of Calgary provides this geospatial data in good faith, but provides no warranty, nor accepts any liability arising from incorrect, incomplete or misleading information or its improper use.

